

WHAT IS CLAIMED IS:

1. A method of trimming a balloon of a balloon catheter, the method comprising:

5 creating protrusions on the balloon by wrapping a member around the balloon such that spaced-apart loops of the member wrapped around the balloon compress the balloon leaving uncompressed portions of the balloon between the spaced apart loops of the member wrapped around the balloon to form the protrusions on the balloon;

leaving the member wrapped around the balloon for a predetermined period of time; and

10 removing the member from the balloon after the predetermined period of time.

2. The method according to claim 1, further comprising heating the balloon during at least one of the creating protrusions on the balloon by wrapping the member around the balloon and the leaving the member wrapped around the balloon for the predetermined period of time.

15

3. The method according to claim 2, wherein the member wrapped around the balloon is constructed of one of polytetrafluorethylene and polyurethane.

20

4. The method according to claim 3, further comprising folding the balloon prior to the creating protrusions on the balloon by wrapping the member around the balloon.

25 5. The method according to claim 4, further comprising the following steps prior to the creating protrusions on the balloon by wrapping the member around the balloon:

introducing a tube of balloon material into a balloon forming mold;

forming the tube of balloon material into a balloon shape; and

30

taking the balloon out of the mold.

6. The method according to claim 5, further comprising attaching the balloon to a catheter tubing.

7. The method according to claim 6, wherein  
5 the folding of the balloon, the creating protrusions on the balloon by wrapping the member around the balloon and the removing the member from the balloon after the predetermined period of time are achieved manually.

8. The method according to claim 6, wherein  
10 the folding of the balloon, the creating protrusions on the balloon by wrapping the member around the balloon and the removing the member from the balloon after the predetermined period of time are achieved by a machine.

9. The method according to claim 1, wherein  
15 the member wrapped around the balloon is constructed of one of polytetrafluorethylene and polyurethane.

10. The method according to claim 1, further comprising  
20 folding the balloon prior to the creating protrusions on the balloon by wrapping the member around the balloon.

11. The method according to claim 10, further comprising the following steps prior to the creating protrusions on the balloon by wrapping the member around the balloon:

25 introducing a tube of balloon material into a balloon forming mold;  
forming the tube of balloon material into a balloon shape; and  
taking the balloon out of the mold.

12. The method according to claim 11, further comprising  
30 attaching the balloon to a catheter tubing.

13. The method according to claim 12, wherein

the folding of the balloon, the creating protrusions on the balloon by wrapping the member around the balloon and the removing the member from the balloon after the predetermined period of time are achieved manually.

5           14.     The method according to claim 12, wherein  
the folding of the balloon, the creating protrusions on the balloon by wrapping the member around the balloon and the removing the member from the balloon after the predetermined period of time are achieved by a machine.

10           15.     The method according to claim 1, further comprising the following steps prior to the creating protrusions on the balloon by wrapping the member around the balloon:

introducing a tube of balloon material into a balloon forming mold;  
forming the tube of balloon material into a balloon shape; and  
15           taking the balloon out of the mold.

16.     The method according to claim 1, further comprising  
attaching the balloon to a catheter tubing.

20           17.     The method according to claim 1, wherein  
the creating protrusions on the balloon by wrapping the member around the balloon and the removing the member from the balloon after the predetermined period of time are achieved manually.

25           18.     The method according to claim 1, wherein  
the creating protrusions on the balloon by wrapping the member around the balloon and the removing the member from the balloon after the predetermined period of time are achieved by a machine.

30           19.     A balloon catheter comprising:  
a foldable and expandable balloon having protrusions on the balloon, the protrusions being created by

wrapping a member around the balloon such that spaced-apart loops of the member wrapped around the balloon compress the balloon leaving uncompressed portions of the balloon between the spaced apart loops of the member wrapped around the balloon to form the protrusions on the balloon;  
leaving the member wrapped around the balloon for a predetermined period of time; and  
removing the member from the balloon after the predetermined period of time.

20. The balloon catheter according to claim 19, wherein the balloon is heated during at least one of the wrapping the member around the balloon and the leaving the member wrapped around the balloon for the predetermined period of time.